



TLS Vanity Units Specification - Type 1

Product:	Vanity Units.
Vanity Top:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Vanity Top:	13mm Solid Grade Laminate (SGL).
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Vanity Top:	13mm Solid Surface.
Core:	Composite material made of minerals and acrylic polymer, allowing it to be thermoformed at around 150 degrees Celsius.
Type:	550mm deep top bed with bull nose front edge (bespoke widths possible).
Subframe:	Built on site to suit site requirements from PAR Vac treated softwood.
Flashgaps/Panels:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Flashgaps/Panels:	13mm Solid Grade Laminate (SGL)
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Unit Height:	Upto 800mm high.
Colours:	TLS Colours to be chosen from Washroom colour selector.
HPL Panels Edge:	Partitions to be square edged and lipped with a 2mm PVC.
SGL Panels Edge:	Machined and CNC finished.
Fixing:	By TLS approved methods to achieve correct finish. TLS to work with builders so they install correctly, including drawings for approval and site measure.
Extras:	Access panels can be hinged and lockable.
Drawings:	Full working drawings to be produced by TLS for comment and approval by Main Contractor.
Supplier:	Total Laminate Systems Ltd, 11 Nimrod Way, East Dorset Trade Park, Wimborne, Dorset BH21 7SH
Contact No:	01202 877 600
Contact Email:	sales@total-laminate.co.uk

TOTAL LAMINATE SYSTEMS LTD.

Unit 11 Nimrod Way, East Dorset Trade
Park, Wimborne, Dorset, BH21 7SH

Tel: **01202 877600**

email: **sales@total-laminate.co.uk**

www.total-laminate.co.uk



TLS Vanity Units Specification - Type 2

Product:	Vanity Units.
Vanity Top:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Vanity Top:	13mm Solid Grade Laminate (SGL).
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Vanity Top:	13mm Solid Surface.
Core:	Composite material made of minerals and acrylic polymer, allowing it to be thermoformed at around 150 degrees Celsius.
Type:	550mm deep top bed with bull nose front edge (bespoke widths possible).
Downstead:	120mm deep, downstand (bespoke depths possible).
Subframe:	Built on site to suit site requirements from PAR Vac treated softwood.
Flashgaps/Panels:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Flashgaps/Panels:	13mm Solid Grade Laminate (SGL)
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Unit Height:	Upto 800mm high.
Colours:	TLS Colours to be chosen from Washroom colour selector.
HPL Panels Edge:	Partitions to be square edged and lipped with a 2mm PVC.
SGL Panels Edge:	Machined and CNC finished.
Fixing:	By TLS approved methods to achieve correct finish. TLS to work with builders so they install correctly, including drawings for approval and site measure.
Extras:	Access panels can be hinged and lockable.
Drawings:	Full working drawings to be produced by TLS for comment and approval by Main Contractor.
Supplier:	Total Laminate Systems Ltd, 11 Nimrod Way, East Dorset Trade Park, Wimborne, Dorset BH21 7SH
Contact No:	01202 877 600
Contact Email:	sales@total-laminate.co.uk

TOTAL LAMINATE SYSTEMS LTD.

Unit 11 Nimrod Way, East Dorset Trade
Park, Wimborne, Dorset, BH21 7SH

Tel: **01202 877600**

email: **sales@total-laminate.co.uk**

www.total-laminate.co.uk



TLS Vanity Units Specification - Type 3

Product:	Vanity Units.
Vanity Top:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Vanity Top:	13mm Solid Grade Laminate (SGL).
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Vanity Top:	13mm Solid Surface.
Core:	Composite material made of minerals and acrylic polymer, allowing it to be thermoformed at around 150 degrees Celsius.
Type:	550mm deep top bed with bull nose front edge (bespoke widths possible).
Downstead:	120mm deep, downstand (bespoke depths possible).
Subframe:	Built on site to suit site requirements from PAR Vac treated softwood.
Flashgaps/Panels:	High-Pressure Laminate (HPL).
Core:	19-20mm Moisture-Resistant MDF board.
Flashgaps/Panels:	13mm Solid Grade Laminate (SGL)
Core:	Compressed multiple layers of kraft paper impregnated with phenolic resin and topped with a decorative surface layer.
Unit Height:	Upto 800mm high.
Colours:	TLS Colours to be chosen from Washroom colour selector.
HPL Panels Edge:	Partitions to be square edged and lipped with a 2mm PVC.
SGL Panels Edge:	Machined and CNC finished.
Fixing:	By TLS approved methods to achieve correct finish. TLS to work with builders so they install correctly, including drawings for approval and site measure.
Extras:	Access panels can be hinged and lockable.
Drawings:	Full working drawings to be produced by TLS for comment and approval by Main Contractor.
Supplier:	Total Laminate Systems Ltd, 11 Nimrod Way, East Dorset Trade Park, Wimborne, Dorset BH21 7SH
Contact No:	01202 877 600
Contact Email:	sales@total-laminate.co.uk

TOTAL LAMINATE SYSTEMS LTD.

Unit 11 Nimrod Way, East Dorset Trade
Park, Wimborne, Dorset, BH21 7SH

Tel: **01202 877600**

email: **sales@total-laminate.co.uk**

www.total-laminate.co.uk